



**SPECIFICATION**  
 Current Rating: 5A  
 Withstanding Voltage: 1000V For One Minute  
 Insulation Resistance: 1000 Megaohms Min. At 500V DC  
 Operating Temperature: -50°C ~ +105°C  
 Contact: Brass, Gold Flash On Contact Area,  
 Tin Plated On Solder Tail, Under Plated Nickel  
 Insulator: PBT+30% Glass Fiber, UL94V-0  
 Shell: Steel, Front Nickel After Tin Plated  
 RoHS Compliant

Pin	A	B	C	D	E
15	30.80	25.00	16.92	19.20	2.29
26	39.20	33.30	25.25	27.70	2.29
44	53.05	47.04	38.96	41.10	2.29
62	69.40	63.50	55.42	57.30	2.41



CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE					
PART No. 70 01 XX HD		CHECKED BY		.X ±0.25 .X* ±3*					
DRAWING No.		DRAWING BY		.XX ±0.15 .XX* ±1*					
				.XXX ±0.05 .XXX* ±0.5*					
SCALE	NONE	REV.	A0	UNIT	mm	NO. REV.	A0	NEW RELEASE	06/17/2008
								REVISIONS	CHK DATE