



Cover



Strain Relief

SPECIFICATION

Current Rating:3 Amp
 Voltage Rating:250V AC/Rms 60Hz
 Dielectric Withstanding Voltage:
 1000V AC/Rms 60Hz For 1 Minute
 Contact Resistance:20 Milliohms Max At 1Amp DC
 Insulator Resistance:1000Megohms At 500V DC
 Contact:Brass
 Housing:Glass-Filled Thermoplastic PBT, UL 94V-0
 Shell:Steel,Tin Over Copper
 Clinch Nut:Brass,Nickel Plated
 RoHS Compliant

Pin	A	B	C	D	E
9	30.81	24.99	16.33	11.08	10.16
15	39.20	33.30	24.66	19.39	17.78
25	53.05	47.04	38.38	33.24	30.48
37	69.40	63.50	54.84	49.86	45.72



CATEGORY		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.38 .X ±0.25 .XX ±0.13 X.' ±3.0' .X' ±1.0'
PART No. 70 06 XX		MEI		
DRAWING No.		CHECKED BY HZF		
		DRAWING BY XYH		
SCALE	NONE	REV.	BO	UNIT mm

NO. REV.	BO	NEW RELEASE	11/18/2008
		REVISIONS	DATE
		CHK	