



Product: <u>8641</u> ☑

Electronic, 2 C #24 Str TC, PE Ins, OS, PVC Jkt, CM

😭 Request Sample

Product Description

Electronic, 2 Conductor 24AWG (7x32) Tinned Copper, PE Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:	low voltage analog signals (4-20ma, 0-10v,); low voltage digital control (24v,); line level audio; computer communication; panel wiring
ealable / ppilealerie.	ion forage analog olgrado (1 zonia, e for,), ion forage alguar control (2 ri,), into foror adato, compater commandatori, parter minig

Construction Details

Conductor

Element	Number of Element	Size	Stranding	Material
Pair(s)	1	24 AWG	7x32	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Color Code
Pair(s)	PE - Polyethylene	0.017 in (0.43 mm)	Black & Clear

Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC

Outer Jacket

Material	Nom. Thickne	ss	Nom. Diameter
PVC - Polyvinyl Chloride	0.025 in (0.64 r	nm)	0.168 in (4.27 mm)
Overall Cable Diameter (Nominal):			68 in (4.27 mm)

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedence	Max. Current
Pair(s)	25 Ohm/1000ft (82 Ohm/km)	22 pF/ft (72 pF/m)	42 pF/ft (140 pF/m)	80 Ohm	2.2 Amps per Conductor at 25°C

Voltage

```
UL Voltage Rating
300 V (CM), 300 V (UL AWM 2092)
```

Mechanical Characteristics

Temperature

UL Temperature	Operating	
60°C (UL AWM 2092)	-20°C to +80°C	

Bend Radius

Stationary Min.	Installation Min.	
1.7 in (43 mm)	1.7 in (43 mm)	

Max. Pull Tension:	11 lbs (5.0 kg)
Bulk Cable Weight:	12 lbs/1000ft (18 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor
Sustainability:	CA Prop 65
Flammability / Reaction to Fire:	UL1685 UL Loading, FT1, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CM
AWM Compliance:	AWM 2092
CEC / C(UL) Compliance:	СМ
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	88641, 82641

History

Update and Revision:

Revision Number: 0.371 Revision Date: 02-08-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
8641 060100	Chrome	Reel	100 ft	612825213765
8641 060500	Chrome	Reel	500 ft	612825213789
8641 060U500	Chrome	UnReel	500 ft	612825213758
8641 0601000	Chrome	Reel	1,000 ft	612825213772
8641 060U1000	Chrome	UnReel	1,000 ft	612825213741
8641 0605000	Chrome	Reel	5,000 ft	612825213796

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.