


YJ57084

Foundation Fieldbus/Profibus PA Application



DESCRIPTION:

1 Pair, 18AWG stranded (7x26), tinned copper conductors, Polyolefin insulation, Overall Beldfoil® shield with tinned copper drain wire, PET Separator tape, overall PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
Conductor Stranding	7 x 26
Cross-sectional Area	18 AWG
Conductor Material	TC – Tinned Copper

INSULATION:

Insulation Material	PO – Polyolefin
Nom. Insulation Diameter	2.2 mm

OVERALL CABLING:

Overall Cabling Lay Length	63 mm
Color Code	Blue and Orange

OVERALL SHIELD:

Overall Shield Type	Tape
Overall Shield Material	Aluminum Foil Polyester Tape
Overall Shield Coverage (%)	100
Drain Wire Conductor Material	TC - Tinned Copper
Overall Separator Material	PET - Polyester Tape
Overall Separator Coverage (%)	100

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Nom. Outer Jacket Wall Thickness	1.1 mm

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	7.0 mm
--------------------------	--------

MECHANICAL CHARACTERISTICS:

Temperature Rating	- 20°C To + 70°C
Min. bending radius	15 x Cable Diameter

YJ57084

Foundation Fieldbus/Profibus PA Application

APPLICABLE STANDARDS:

EU RoHS Compliant (Y/N)	Y
EU RoHS Compliance Date	June 2007
Electrical Characteristics	IEC 61158-2, Type A

FLAME TEST:

Flame Test	IEC 60332-1
------------	-------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS ACCORDING TO IEC 61158-2

Max. Conductor DC Resistance	23.2 Ω /km
Impedance@ 31.25KHz	100 \pm 20 Ω
Nom. Mutual capacitance core-core @1KHz	78.7 pF/m
Max. Capacitance Unbalance	3.94 pF/m
Nom. Mutual capacitance core-shield @1KHz	147.6 pF/m
Nom. Velocity of Propagation	66 %
Max. Attenuation @ 39KHz	0.3 dB/100m
Voltage Rating	300V

PUT-UPS AND COLORS:

Item	Description	Put-Up (M)	Cable Weight (kg)	Jacket Color
YJ57084 003 500M	1P #18 PP SH PVC	500	33	Orange
YJ57084 003 1000M	1P #18 PP SH PVC	1000	67	Orange
YJ57084 003 1500M	1P #18 PP SH PVC	1500	100	Orange

Revision Number: 3

Revision Date: 2014-12-22

©Copyright 2009 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.