

Product information

13 66 180 T

KNIPEX StriX

IEC 60900 DIN EN 60900



- for single, multiple and fine stranded conductors with plastic or rubber insulation up to 5.0 mm dia. or 10 mm² cable cross-section
- Increments in the jaw provide a visual orientation aid for stripping consistent lengths (11 mm and 16 mm)
- easy adjustment to the required diameter of solid or stranded wire with knurled screw and lock nut
- Shear blade for cutting copper and aluminium cable up to Ø 15 mm (5 x 2.5 mm²)
- slim dimensions for easy access
- bolted joint: precise, zero backlash operation of pliers
- Pliers with integrated, insulated tether attachment point for a tool tether
- High-grade special tool steel, forged, multi stage oil-hardened

Allgemein	
Article No.	13 66 180 T
EAN	4003773081906
Pliers	chrome plated
Head	chrome plated
Handles	insulated with multi-component grips, VDE-tested with integrated insulated tether attachment point for a tool tether
weight	240 g
Dimensions	180 x 52 x 27 mm

Technische Attribute	
Cutting capacity copper cable, multiple-stranded	Ø 50 mm ²
Cutting capacity copper cable, multiple-stranded	Ø 15 mm
Stripping capacities in square millimetres	10 mm ²
Stripping capacities (diameter)	Ø 5 mm
AWG	8
Drop Protection System	yes
VDE tested	yes

Klassifikation	
eCl@ss 5.1.4	21040302
ETIM 5.0	EC000163
ETIM 6.0	EC000163
proficl@ss 6.0	AAA002c003

technical change and errors excepted