

Product information

73 06 160 SB

KNIPEX X-Cut®

DIN ISO 5749 IEC 60900 DIN EN 60900



- cuts finest strands as well as multi-core cables and piano wires
- Powerful, light and universal
- high cutting performance with minimum effort due to optimum coordination of the cutting edge angle and transmission ratio
- box-joint design: highest stability with low weight
- doubly supported joint axis for heavy duty
 large opening width for thicker cables
- cuts precisely, even through fine copper wires
- compact, low-weight construction
- universally usable, in the assembly, maintenance and production
- 40% less force required compared with standard diagonal cutters of the same length
- Chrome vanadium heavy-duty steel, forged, multi stage oil-hardened

Allgemein

·	
Article No.	73 06 160 SB
EAN	4003773075363
Pliers	chrome plated
Head	chrome plated
Handles	insulated with multi-component grips, VDE-tested
weight	208 g
Dimensions	160 x 115 x 92 mm
Technische Attribute	
Cutting capacities medium hard wire (diameter)	Ø 3.8
Cutting capacities hard wire (diameter)	Ø 2.7
Cutting capacities piano wire (diameter)	Ø 2.2
Cutting capacity copper cable, multiple- stranded	Ø 12.0
Cutting capacities soft wire (diameter)	Ø 4.8 mm
VDE tested	yes
Klassifikation	
eCl@ss 5.1.4	21040302
ETIM 5.0	EC000165
ETIM 6.0	EC000165
proficl@ss 6.0	AAA949c004

technical change and errors excepted