

## Product information

# 74 06 250 T

## High Leverage Diagonal Cutter

DIN ISO 5749 IEC 60900 DIN EN 60900

- with integrated forged axle for heavy duty
- suitable for all types of wire including piano wire
- high cutting performance with minimum effort due to optimum co-ordination of the cutting edge angle and transmission ratio
- precision cutting edges additionally induction-hardened, cutting edge hardness approx. 64 HRC
- Pliers with integrated, insulated tether attachment point for a tool tether
- Chrome vanadium heavy-duty steel, forged, multi stage oil-hardened



Allgemein	
Article No.	74 06 250 T
EAN	4003773081500
Pliers	chrome plated
Head	chrome plated
Handles	insulated with multi-component grips, VDE-tested with integrated insulated tether attachment point for a tool tether
weight	490 g
Dimensions	250 x 98 x 30 mm

Technische Attribute	
Style	0
Cutting capacities medium hard wire (diameter)	Ø 4.6
Cutting capacities hard wire (diameter)	Ø 3.5
Cutting capacities piano wire (diameter)	Ø 3.0
Drop Protection System	yes
VDE tested	yes

Klassifikation	
eCl@ss 5.1.4	21040302
ETIM 5.0	EC000165
ETIM 6.0	EC000165
proficl@ss 6.0	AAA949c004

*technical change and errors excepted*