

## Product information

# 87 02 180 SB

## KNIPEX Cobra®

DIN ISO 8976



- push the button for adjustment on the workpiece: fast and comfortable handling
- fine adjustment: ensures optimum adjustment to differently sized workpieces and user-friendly handle position
- reliable catching of the hinge bolt: no unintentional shifting
- box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- one-hand adjustment
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- Chrome vanadium electric steel, forged, multi stage oil-hardened

| Allgemein                       |                            |
|---------------------------------|----------------------------|
| Article No.                     | 87 02 180 SB               |
| EAN                             | 4003773047001              |
| Pliers                          | grey atramentized          |
| Head                            | polished                   |
| Handles                         | with multi-component grips |
| weight                          | 218 g                      |
| Dimensions                      | 180 x 113 x 22 mm          |
| Technische Attribute            |                            |
| Adjustment positions            | 18                         |
| Capacities for nuts             | 1 1/2                      |
| Capacities for nuts             | 36 mm                      |
| Capacities for pipes (diameter) | Ø 42 mm                    |
| Klassifikation                  |                            |
| eCl@ss 5.1.4                    | 21040301                   |
| ETIM 5.0                        | EC000164                   |
| ETIM 6.0                        | EC000164                   |
| proficl@ss 6.0                  | AAA936c004                 |

*technical change and errors excepted*