

Product information

87 02 250 T

KNIPEX Cobra®

DIN ISO 8976



- push the button for adjustment on the workpiece: fast and comfortable handling
- fine adjustment: ensures optimum adjustment to differently sized workpieces and user-friendly handle position
- reliable catching of the hinge bolt: no unintentional shifting
- box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- one-hand adjustment
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- pliers with tether attachment point for mounting a fall protection
- Chrome vanadium electric steel, forged, multi stage oil-hardened

Allgemein

Article No.	87 02 250 T
EAN	4003773080152
weight	390 g
Dimensions	250 x 60 x 18 mm

Technische Attribute

Adjustment positions	25
Capacities for nuts	2
Capacities for nuts	46 mm
Capacities for pipes (diameter)	Ø 50 mm

Klassifikation

eCl@ss 5.1.4	21040301
ETIM 5.0	EC000164
ETIM 6.0	EC000164
proficl@ss 6.0	AAA936c004

technical change and errors excepted