

## **Product information**

## 87 11 250 SB

## KNIPEX Cobra®...matic

**DIN ISO 8976** 



- the proved "Cobra" with automatic adjustment
- the pliers can be opened and adjusted directly at the workpiece with one hand
- the "Cobra..matic" closes when pushing a button
- the integrated spring of the automatic adjustment is shielded in the handles
- gripping surfaces with special hardened teeth, teeth hardness approx.
  61 HRC: high wear resistance and stable gripping
- fine adjustment: ensures optimum adjustment to differently sized workpieces and user-friendly handle position
- reliable catching of the hinge bolt: no unintentional shifting
- box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- Chrome vanadium electric steel, forged, multi stage oil-hardened

Allgemein	
Article No.	87 11 250 SB
EAN	4003773022114
Pliers	grey atramentized
Head	polished
Handles	with non-slip plastic coating
weight	357 g
Dimensions	250 x 113 x 87 mm

Technische Attribute	
Adjustment positions	25
Capacities for pipes (diameter)	Ø 2
Capacities for pipes (diameter)	Ø 50 mm
Capacities for nuts	46 mm

Klassifikation	
eCl@ss 5.1.4	21040301
ETIM 5.0	EC000164
ETIM 6.0	EC000164
proficl@ss 6.0	AAA936c004

technical change and errors excepted