

Product information

87 21 300

KNIPEX Cobra® QuickSet

DIN ISO 8976



- Fully open, push, grab!
- additional fast adjustment on the workpiece by sliding the pliers handle
- combines the proven, reliable locking of the hinge bolt with an additional push function which makes it easier to work in very confined and inaccessible areas
- the adjustment directly on the workpiece is possible by simply sliding
 the pliers handle
- reliable locking of the hinge bolt with the first workload. The gripping width of the pliers is then fixed and can only be adjusted by pressing the button.
- to re-activate the sliding function, the hinge bolt must be released by pressing the push button and the pliers must be completely opened again
- Chrome vanadium electric steel, forged, multi stage oil-hardened

Allgemein

| • | |
|---------------------------------|-------------------------------|
| Article No. | 87 21 300 |
| EAN | 4003773078524 |
| Pliers | grey atramentized |
| Head | polished |
| Handles | with non-slip plastic coating |
| weight | 545 g |
| Dimensions | 300 x 123 x 19 mm |
| Technische Attribute | |
| Adjustment positions | 25 |
| Capacities for pipes (diameter) | Ø 2 3/4 |
| Capacities for nuts | 60 mm |
| Capacities for pipes (diameter) | Ø 70 mm |
| Klassifikation | |
| eCl@ss 5.1.4 | 21040301 |
| ETIM 5.0 | EC000164 |
| ETIM 6.0 | EC000164 |
| proficl@ss 6.0 | AAA936c004 |
| | |

technical change and errors excepted