

## **Product information**

## 88 06 250 SB

## **KNIPEX Alligator®**

DIN ISO 8976 IEC 60900 DIN EN 60900



- good access to the workpiece due to slim size of head and joint area
- more output and comfort compared to conventional water pump pliers of the same length: 9-notch adjustment positioning for 30 % more gripping capacity
- box-joint design for high stability due to double guide
- self-locking on pipes and nuts: no slipping on the workpiece and low handforce required
- guard prevents operators' fingers being pinched
- favourable lever action: optimum transmission of force
- gripping surfaces with special hardened teeth, teeth hardness approx. 61 HRC: high wear resistance and stable gripping
- Chrome vanadium electric steel, forged, multi stage oil-hardened

All	gemein
	3

Article No.	88 06 250 SB
EAN	4003773034292
Pliers	chrome plated
Head	chrome plated
Handles	insulated with multi-component grips, VDE-tested
weight	396 g
Dimensions	250 x 84 x 92 mm
Technische Attribute	
Adjustment positions	9
Capacities for pipes (diameter)	Ø 2 Inch
Capacities for nuts	46 mm
Capacities for pipes (diameter)	Ø 50 mm
VDE tested	yes
Klassifikation	
eCl@ss 5.1.4	21040301
ETIM 5.0	EC000164
ETIM 6.0	EC000164
proficl@ss 6.0	AAA936c004

technical change and errors excepted